



Ref.	Dimensions (mm)
Flange	F14
D x depth	M16X24
F	140
B	36
O	38.5
A	1036.1
G	19.5
I	27
L	216
M	101.5
N	114.5
P	84.5
Q	101.5
R	41
S	30
T	186
U	399
V	400
Y	365.6
W	1/4" GAS
Z	637.1
Ch 1	36
Ch 2	40
Ancillaries Attachment	AA2

Spring return Actuators Normally Closed (N.C.) - Output Torque related to rotation angle, in Nm (0° valve closed 90° valve open)

Spring Torque				Air pressure supply in bar																														
SIZE				2,4			2,8			3			3,5			4,2			5			5,6			6			7			8			
	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°	0°	50°	90°				
2,8	240.0	180.0	360.0	274.3	128.6	154.3	360.0	180.0	240.0	402.9	205.7	282.9	510.0	270.0	390.0	660.0	360.0	540.0																
3,5	300.0	225.0	450.0							342.9	160.7	192.9	450.0	225.0	300.0	600.0	315.0	450.0	771.4	417.9	621.4	900.0	495.0	750.0										
4,2	360.0	270.0	540.0										390.0	180.0	210.0	540.0	270.0	360.0	711.4	372.9	531.4	840.0	450.0	660.0	925.7	501.4	745.7	1140	630.0	960.0	1354.3	758.6	1174	
5,6	480.0	360.0	720.0																591.4	282.9	351.4	720.0	360.0	480.0	805.7	411.4	565.7	1020	540.0	780.0	1234.3	668.6	994.3	

Technical Data

Max Pressure	** Min Pressure	Rotation	Stroke Adjustment	Screw Stroke Adjustment	*Moving time (sec.)		Operating temperature (°C)
					Opening	Closing	
8.4 bar	1 bar	92° -1° +91°	Not available	-	2.2	2.5	Standard -20°C +80°C High temperature -20°C +150°C Low temperature -50°C +60°C

Weight Kg	Chamber Ø (mm)	Air volume L/cycle	Theoretical n° of turns to close/open starting from neutral position	Rim pull force (N) to obtain the nominal torque	Maximum flange torque values
38.8	145	4.31	25	133.5	F14 = 2000 Nm

****Attention:**
for "High Temperature"
and "Low Temperature" version,
the Min Pressure is 3 bar.

*The moving time could vary on different operating and installation factors.

Operating Medium

The operating medium shall have a dew point equal to -20 °C or, to be at least, 10 °C below the ambient temperature (ISO 8573-1, Class 3).
The maximum particle size shall not exceed 40 µm (ISO 8573-1, Class 5).